

FILE NO.: S401012

S401016
S401025
S021012
S021016



MATERIAL SAFETY DATA SHEET

OUT THE DOOR TOPCOAT

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Out The Door Topcoat
CHEMICAL NAME: Nail Lacquer
CHEMICAL FAMILY: Topcoat
PRODUCT USE: Nail Topcoat
EMERGENCY PHONE: Info-Trac 1-352-323-3500

MANUFACTURER: International Nail Manufacturers (inm)
DIVISION: Nail Cartel, Inc.
ADDRESS: 1221 N. Lakeview Ave.
PHONE: 714-779-9892
FAX: 714-779-9971

MSDS DATE: 4/20/2011

PREPARED BY: Garret Kellenberger-Production Manager

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	CAS Numbers	Exposure OSHA	Limits ACGIH	Percentage
Ethyl Acetate	141-78-6	200 ppm	400 ppm	35-40
SD Alcohol 40B	64-17-5	N/DA	N/DA	15-20
Butyl Acetate	123-86-4	150 ppm	200 ppm	15-20
Cellulose Acetate Butyrate	9004-36-8	N/DA	N/DA	10-15
Acrylates Polymer	25035-69-2	N/DA	N/DA	1-5
Trimethyl Pentalyl Biisobutyrate	6846-50-0	N/DA	N/DA	1-5
Sucrose Benzoate	12738-64-6	N/DA	N/DA	1-5
Triphenyl Phosphate	115-86-6	N/DA	N/DA	1-5
Nitrocellulose	9004-70-0	N/DA	N/DA	1-5
Isopropyl Alcohol	108-21-4	400 ppm	500 ppm	<1
Benzophenone-1	131-56-6	N/DA	N/DA	<1
Dimethyl Polysiloxane	9006-65-9	N/DA	N/DA	<1
D&C Violet #2 (CI60725)	81-48-1	N/DA	N/DA	<1
FD&C Blue #1 (CI42090)	3844-45-6	N/DA	N/DA	<1

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information is based on finding from related or similar materials.

- Flammable Liquid and Vapor!
- May cause eye irritation.
- May cause respiratory irritation.
- Please read entire MSDS for additional information.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Inhalation, skin, and eye contact.
Eyes: Exposure causes eye irritation. Symptoms include stinging, tearing, redness, and swelling.
Skin: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns.
Ingestion: Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.
Inhalation: Vapor and mist are irritating to mucous membrane. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.
Sub-Chronic Effects: It may cause headaches, nausea, vomiting, and narcotic effect if over-exposed.
NOTE: Refer to Section 11, Toxicological Information for Details.

MATERIAL SAFETY DATA SHEET

FILE NO.: S401012

S401016
S401025
S021012
S021016



OUT THE DOOR TOPCOAT

SECTION 4: FIRST AID MEASURES

First Aid for Eye: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with clean water while holding eyelids apart. If symptoms persist or if there is any visual difficulty, seek medical attention.

First Aid for Skin: Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.

First Aid for Ingestion: If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

First Aid for Inhalation: Remove to fresh air. If having breathing difficulty, give oxygen. Seek medical attention if discomfort persists.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
-4°C	0.5 Lower/12 Upper	

Method:

Extinguishing Media: Foam, dry chemical, cold water spray.

Fire Fighting Instructions: Wear Self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION! Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, Carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Release Procedures: Eliminate all sources of heat and ignition. Use an absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g. vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

SECTION 7: HANDLING AND STORAGE

Handling: Keep containers cool and dry. Keep away from heat, light, and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Store in a well ventilated area. Allow some air space above liquid level. Keep containers closed when not in use.

Explosion Hazard: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR 1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/Face Protection: Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suite. Nitrile rubber is better than PVC.

Skin Protection: Wear resistant gloves to prevent repeated or prolonged skin contact. Wear impervious clothing and boots.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear A NIOSH/MSHA or European Standard EN 149

MATERIAL SAFETY DATA SHEET

FILE NO.: S401012

S401016
S401025
S021012
S021016



OUT THE DOOR TOPCOAT

approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.
Follow OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile
Clear Viscous liquid	Ester Odor	N/DA	N/DA	N/DA	72-76

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility in Water
Undefined	N/DA	N/DA	N/DA	NDA	N/DA	N/DA	Insoluble

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
-4°C	N/DA	N/DA

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Incompatibility (Materials to Avoid) Alkaline, strongly acidic and amine substances.

Hazardous Decomposition Products: N/DA

Harardous Polymerization: Will not occur

Conditions to Avoid: Direct sunlight.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation-Skin	Irritation-Eye
No information available	No information available	No information available	No information available	No information available

Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non-allergic dermatitis upon repeated prolonged contact. Vapor from solvents may cause: ill effects to the renal system; central nervous system problems; irritation to the respiratory tracts and other various mucosal membranes.

SECTION 12: ECOLOGICAL INFORMATION

Product should not be allowed to enter drains or watercourses. Used in large volumes this product may incur the requirements of the Environmental Protection Act (pollution control/air).

SECTION 13: DISPOSAL CONSIDERATIONS

Treat as for spillages.

Wear appropriate protection; see Storage and Handling, Accidental Release Measures section.

Product must be disposed of by an authorized waste disposal firm in accordance with the local authorities regulation. Empty containers should be treated as above.

SECTION 14: TRANSPORT INFORMATION

DOT (49 CFR 172)	
Proper Shipping Name:	UN1263, Nitrocellulose Lacquer, 3, PGII
Identification #	UN1263
Marine Pollutant:	Yes
Special Provisions:	
Emergency Response Guidebook (ERG) #	
IATA (DRG)	
Proper Shipping Name:	UN1263, Nitrocellulose Lacquer, 3, PGII
Class or Division:	3
UN or ID Number:	UN1263
Packaging Instructions:	
Emergency Response Guidance (ICAO) #:	
IMO (IMDG)	
Proper Shipping Name:	UN1263, Nitrocellulose Lacquer, 3, PGII
Class or Division:	3.2

MATERIAL SAFETY DATA SHEET

FILE NO.: S401012

S401016
S401025
S021012
S021016



OUT THE DOOR TOPCOAT

UN or ID Number	UN1263
Special Provisions & Stowage/Segregation	
Emergency Schedule (EmS) #:	
Other Information	

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: • NONE There are no ODS's (ozone depleting substances) as defined by the U.S. Clean Air Act.
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: • Butyl Acetate, CAS# 123-86-4
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as in indirect food-packaging additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. It's hazards are: • Immediate (acute) health hazard. • Fire hazard
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA (40CFR 261): • Ethyl Acetate CAS# 141-78-6, RCRA Code: U112 • May contain Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substance that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List) • Ethyl Acetate CAS# 141-78-6, RQ (Lbs) 5000 • Butyl Acetate, CAS# 123-86-4, RQ (Lbs) 5000
SARA Title III: Section 311-312	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are: • Immediate (acute) health hazard • Fire hazard
SARA Title III: Section 313	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: • NONE
TSCA Section 8 (b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemical in this material have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4
NJ Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4
PA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4
FL Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4
MN Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Butyl Acetate CAS# 123-86-4

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl Acetate CAS# 141-78-6 is on the DSL list. WHMIS = B2, D2B Isopropyl Alcohol CAS# 67-63-0 is on the DSL list. WHMIS = B2, D2B Butyl Acetate CAS# 123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B Nitrocellulose CAS# 9004-70-0 is on the DSL list. WHMIS = B4, D2B, F
EINECS: European Einventory	OTD Topcoat: • HAZARD SYMBOLS: Xn, F: Harmful, Highly Flammable • RISK PHRASES: R11: Highly flammable, R20: Harmful by inhalation, R36/37/38 Irritating to eyes, respiratory system and skin • SAFETY PHRASES: S7/9: Keep container tightly closed and in a well ventilated place, S16: Keep away from sources of ignition-no smoking, S23: Do not breathe vapor, S24/25: In case of contact with eyes, rinse

MATERIAL SAFETY DATA SHEET

FILE NO.: S401012

S401016

S401025

S021012

S021016




OUT THE DOOR TOPCOAT

		<p><i>immediately with plenty of water and seek medical advise, S33: take precautionary measure against static discharges, S37/39: wear suitable protective clothing and gloves, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible) S61: Avoid release to the environment.</i></p> <ul style="list-style-type: none">Refer to special instruction/Safety data sheets.
--	--	--

SECTION 16: OTHER INFORMATION

HMIS:



2	Health
3	Flammability
1	Reactivity

DISCLAIMER: The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

international nail manufacturers